Applicability of Construction (Temporary) and Permanent (Post-Construction) Stormwater BMP Requirements (Stormwater Intake Form for all Development Permit Applications)

Form I-1

Project Information

Project Address/Location:

Brief Description of Work Proposed:

Determination of Requirements

Answer each step below. **Upon reaching a Stop, do not complete further Steps beyond the Stop.** If additional forms are required, complete those additional forms and submit them along with this form as a complete set.

Step		Answer	Progression	
Step 1: Does the project consist exclusively of one or		🗆 Yes	Stop.	
both of the activity types below?			No permanent storm water BMP plan	
 Project with no soil disturbance or change to 			is required.	
building general exterior dimensions or structural			Review and sign the Stormwater	
framing. <i>Examples:</i> interior remodeling, electrical work, HVAC work, plumbing, etc.			Certification Statement.	
		🗆 No	Complete and attach Form I-2	
 Routine maintenance. Examples: roof repairs, 				
pavement grinding, resurfacing existing				
roadways, routine replacement of damaged				
pavement (e.g., pothole repair), resurfacing or				
repairing existing sidewalks or pedestrian ramps,				
trenching and resurfacing associated with utility				
work, or rebuilding a structure to its original				
design after a fire or natural disaster.				
Certification				
I certify under penalty of law that this document and all attachments were prepared under my direction				
or supervision in accordance with a system designed to assure that qualified personnel properly gather				
and evaluate the information submitted. Based on my inquiry of the person or persons who manage the				
system, or those persons directly responsible for gathering the information, the information submitted				
is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are				
significant penalties for submitting false information, including the possibility of fine and imprisonment				
for knowing violations. This application is signed under penalty of perjury and does not require				
notarization.				
Name of Person Completing			Date	
this Form			Completed	
Role of Person Completing this	Property Owner	Contrac	tor 🗆 Architect 🗆 Engineer	
Form	Other:			
Signature				

For additional information and to review the BMP Design Manual, visit http://www.lemongrove.ca.gov/departments/development-services/stormwater.

Stormwater Certification Statement

The following stormwater quality protection measures are required by Lemon Grove Municipal Code Chapter 8.48 and the City's Jurisdictional Runoff Management Program.

- 1. All applicable construction BMPs and non-stormwater discharge BMPs shall be implemented in accordance with the City of Lemon Grove minimum BMP requirements included in the City of Lemon Grove Municipal Code and the City of Lemon Grove Jurisdictional Runoff Management Program (JRMP). All stormwater BMPs shall be maintained for the duration of the project.
- 2. Erosion control BMPs shall be implemented for all portions of the project area in which no work has been done or is planned to be done over a period of 14 or more days. All onsite drainage pathways that convey concentrated flows shall be stabilized to prevent erosion.
- 3. Run-on from areas outside the project area shall be diverted around work areas to the extent feasible. Run-on that cannot be diverted shall be managed using appropriate erosion and sediment control BMPs.
- 4. Sediment control BMPs shall be implemented, including providing fiber rolls, gravel bags, or other equally effective BMPs around the perimeter of the project to prevent transport of soil and sediment offsite. Any sediment tracked onto offsite paved areas shall be removed via sweeping at least daily. All BMPs shall be installed and maintained in accordance with the applicable CASQA fact sheets.
- 5. Trash and other construction wastes shall be placed in a designated area at least daily and shall be disposed of in accordance with applicable requirements.
- 6. Materials shall be stored to avoid being transported in storm water runoff and non-storm water discharges. Concrete washout shall be directed to a washout area designed in accordance with CASQA standards; concrete shall not be washed out to the ground.
- 7. Stockpiles and other sources of pollutants shall be covered when the chance of rain within the next 48 hours is at least 50%.

I certify that the stormwater quality protection measures listed above will be implemented at the project described on Form I-1. I understand that failure to implement these measures may result in monetary penalties or other enforcement actions. This certification is signed under penalty of perjury and does not require notarization.

Name:	Title:
Signature:	Date:/

For additional information and to review the BMP Design Manual, visit <u>http://www.lemongrove.ca.gov/departments/development-services/stormwater</u>.